Implicit Surfaces & Polygon Meshes

Polygon Meshes
Implicit Surfaces
Constructive Solid Geometry

5 Apr. 2000

Modeling Complex Shapes

- **We want to build models of very complicated objects**
- **An equation for a sphere is possible, but how about an equation for a telephone, or a face, or a cloud?**
- **Complexity is achieved using simple pieces**
  - **The pieces could be polygons, parametric surfaces, or implicit surfaces**
- **Requirements**
  - **Model *anything* with arbitrary precision (in principle)**
  - **Easy to build and modify**
  - **Efficient computations (for rendering, collisions, etc.)**
  - **Easy to implement (a minor consideration...)**

Polygon Meshes

- **Any shape can be modeled out of polygons**
  - **if you use enough of them…**
- **Polygons with how many sides?**
  - **Can use triangles, quadrilaterals, pentagons, … n-gons**
  - **Triangles are most common.**
  - **When > 3 sides are used, ambiguity about what to do when polygon nonplanar, or concave, or self-intersecting.**



- **Polygon meshes are built out of**
  - ***vertices* (points)**
  - ***edges* (line segments between vertices)**
  - ***faces* (polygons bounded by edges)**

How Many Polygons to Use?



A File Format for Polygon Models: OBJ

```
# OBJ file for a 2x2x2 cube
v -1.0  1.0  1.0   - vertex 1
v -1.0 -1.0  1.0   - vertex 2
v  1.0 -1.0  1.0   - vertex 3
v  1.0  1.0  1.0   - …
v -1.0  1.0 -1.0
v -1.0 -1.0 -1.0
v  1.0 -1.0 -1.0
v  1.0  1.0 -1.0
f 1 2 3 4
f 8 7 6 5
f 4 3 7 8
f 5 1 4 8
f 5 6 2 1
f 2 6 7 3
```

Syntax:

v *x y z* - *a vertex at (x,y,z)*

f $v_1\ v_2\ \ldots\ v_n$
a face with vertices $v_1, v_2, \ldots v_n$

*anything* - *comment*

Frontfacing / Backfacing

- **A polygon has two sides, of course.**
- **It's customary in CG to use the right hand rule to pick one side to call the *front face*.**
- **Counterclockwise = front, clockwise = back**
- **This is important for:**
  - lighting
  - backface culling
  - For the triangle ABC below, the front face is *up*.



Normals and Plane Equations

- **Need normals for shading, plane eqns for intersection tests**
- **A *normal* to a plane is a vector that is perpendicular to that plane (two possible choices)**
- **A plane is specified by a point P and a normal vector N**
- **N•(X-P) = 0 if and only if X lies in the plane; this is an *implicit equation* for the plane**
  - Expand this out: 0 = N•X - N•P = ax + by + cz + d
- **3 vertices define a plane, its normal is: N=(B-A) x (C-A)**
- **Unit normal**

$$\hat{\mathbf{N}} = \mathbf{N} / |\mathbf{N}|$$



Polygon Models in OpenGL

- for faceted shading

```
< calculate face normal n
  using cross product rule >
glNormal3fv(n);
glBegin(GL_POLYGONS);
glVertex3fv(vert1);
glVertex3fv(vert2);
glVertex3fv(vert3);
glEnd();
```

- for smooth shading

```
glBegin(GL_POLYGONS);
glNormal3fv(normal1);
glVertex3fv(vert1);
glNormal3fv(normal2);
glVertex3fv(vert2);
glNormal3fv(normal3);
glVertex3fv(vert3);
glEnd();
```

Data Structures for Polygon Meshes

- **Simplest (but dumb)**
  - `float triangle[n][3][3];` **(each triangle stores 3 (x,y,z) points)**
  - **redundant: each vertex stored multiple times**
- **Vertex List, Face List**
  - **List of vertices, each vertex consists of (x,y,z)**
    geometric (shape) info only
  - **List of triangles, each a triple of vertex id's (or pointers)**
    topological (connectivity, adjacency) info only

  Fine for many purposes, but finding the faces adjacent to a vertex takes O(F) time for a model with F faces. Such queries are important for topological editing.

- **Fancier schemes:**

  Store more topological info so adjacency queries can be answered in O(1) time.

  Winged-edge data structure **– edge structures contain all topological info (pointers to adjacent vertices, edges, and faces).**

  Quad-edge data structure **– a variant of the above.**

What Implicit Functions are Good For



Ray - Surface Intersection Test



Inside/Outside Test

Surfaces from Implicit Functions

- **Constant Value Surfaces are called (depending on whom you ask):**
  - **constant value surfaces**
  - **level sets**
  - **isosurfaces**
- **Nice Feature: you can add them! (and other tricks)**
  - **this merges the shapes**
  - **When you use this with spherical exponential potentials, it's called *Blobs*, *Metaballs,* or *Soft Objects*. Great for modeling animals.**

Blobby Models



- **Implicit function is the sum of Gaussians centered at several points in space, minus a threshold**
- **varying the standard deviations of the Gaussians makes each blob bigger**
- **varying the threshold makes blobs merge or separate**

How to draw implicit surfaces?

- Note: the surface normal is -Grad F = $-\nabla F$
- It's easy to ray trace implicit surfaces
  - (as we'll see later…)
- Volume Rendering can display them
- Convert to polygons: the Marching Cubes algorithm
  - Divide space into cubes
  - Evaluate implicit function at each cube vertex
  - Do root finding or linear interpolation along each edge
  - Polygonize on a cube-by-cube basis

Isosurfaces of Simulated Tornado



Sets of Points, Surfaces and Solids

- Implicit surface: set of all points that satisfy $F(x,y,z)=0$
- The points that satisfy $F(x,y,z)<0$ define a solid (or solids) bounded by the surface
- The solid is directly defined (unlike definitions using parametric surfaces)
- Example
  - An infinitely long (solid) cylinder with radius r:

$$F = x^2 + y^2 - r^2$$

  - To limit cylinder to length L, abs(z) < L/2 and keep the function implicit use max:

$$F = \max\left(\mathrm{abs}(z)-L/2, x^2 + y^2 - r^2\right)$$

- Implicit functions for a cube? Any convex polyhedron?

Constructive Solid Geometry (CSG)

- Generate complex shapes with basic building blocks
  - machine an object - saw parts off, drill holes
  - glue pieces together
- This is sensible for objects that are actually made that way